ANALYSIS OF AIR VOID VARIATIONS WITH TRAFFIC IN HOT MIX ASPHALT WEARING COURSE MIXTURES USED IN SRI LANKAN ROADS – A CASE STUDY

Kottawatta Hewage Ruwin Lakmal

(118856C)



Thesis submitted in partial fulfillment of the requirements for the degree Master of Science

Department of Civil Engineering

University of Moratuwa Sri Lanka

August 2015

Declaration of the candidate and supervisor

I declare that this is my own work and this thesis/dissertation does not incorporate without acknowledgement any material previously submitted for a degree or diploma in any other University or institute of higher learning, and to the best of my knowledge and belief, it does not contain any material previously published or written by another person except where the acknowledgement is made in the text.

Also, I hereby grant to University of Moratuwa the non-exclusive right to reproduce and distribute my thesis/dissertation, in whole or in part, electronic, or other medium. I retain the right to use this content in whole or in part in future works (such as articles and books).



The above candidate has carried out research for the Master thesis under my supervision.

Research Supervisor	Date

Professor W K Mampearachchi

ABSTRACT

Over the past decades, road construction with hot mix asphalt (HMA) has significantly increased. However, many issues have risen with respect to the durability of recently constructed asphalt concrete roads. Therefore, the importance of introducing new quality control measures is a current concern.

Properties of the asphalt mixture and the construction practices are important criteria for quality and durability of asphalt pavements. Present Sri Lankan practice is to measure and control, (1) Thickness, (2) Density, (3) Bitumen content and aggregate gradation, and (4) Roughness index (IRI) of the laid asphalt mat.

Objective of the present research is to find the importance of measuring air void of the laid asphalt mat and the need of a combined index of significant parameters to improve quality and durability of asphalt concrete roads.

Core samples were tested at 12 locations with various initial compaction levels at two aging levels, as 100 days and 225 days. In addition, performance of road sections was evaluated with various levels of initial compaction after 5 years to check the long-term aging of asphalt concrete. It revealed that initial air void content decreased significantly under traffic in a short period and it is not possible to evaluate the long-term performance of HMA roads by initial air void content alone.



Key words: Air voids, Marshall density, Degree of compaction

DEDICATION

This research study is dedicated to my wife Shamalee, my son Thejana, and my daughter Sithuli.



ACKNOWLEDGEMENTS

First, I thank my supervisor Professor Wasantha Mampearachchi, for his guidance and his complete devotion to help me to complete this research. Many a time he put his thoughts in to this research and without his specific advice and help, this work would have never attain such a quality.

Secondly, I am grateful to my employer, MAGA Engineering (Pvt) Ltd., for the facilities and resources provided to continue this research up to completion.

Special thanks are due to the Material Engineer Amila, and all laboratory staff. Their immense help and support made this process easier.

Finally, I wish to thank all others who supported to make this work a success.



TABLE OF CONTENTS

ABSTRACT	i
DEDICATION	ii
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	iv
LIST OF FIGURES	vi
LIST OF TABLES	
LIST OF ABBREVIATIONS	
CHAPTER 1: INTRODUCTION	
1.1 Introduction	
1.2 Research Objective	
CHAPTER 2: LITERATURE REVIEW	
2.1 Hot Mix Asphalt (HMA)	3
2.2 Colomix Asphalt (CMA) Theses & Dissertations	5
2.3 Volumetric of HMAib.mrt.ac.lk	5
2.4 Air voids - Va.	6
2.5 Voids Filled with Asphalt (VFA)	6
2.6 Voids in the Mineral Aggregate (VMA)	8
2.7 Aggregate Gradation	9
2.8 Binder Content	9
2.9 Mat Density	11
2.10 Air Voids	
2.11 HMA Compaction	14
2.12 Effect on the Compaction Process	
2.13 Common Failures in HMA Roads	
2.13.1 Alligator Cracking	
2.13.2 Block Cracking	
2.13.3 Longitudinal (Linear) Cracking	

2.13.4 Transverse Cracking	26
2.13.5 Edge Cracks	27
2.13.6 Joint Reflection Cracks	27
2.13.7 Slippage Cracks	28
2.13.8 Pot Holes	28
2.13.9 Depressions	29
2.13.10 Rutting	29
2.13.11 Shoving	30
2.13.12 Raveling	31
2.13.13 Bleeding	31
CHAPTER 3: EXPERIMENTAL PROCEDURE	33
3.1 Methodology	33
3.1.1 Literature Review	
3.1.2 QA/ QC Practices in HMA Projects	33
3.2 Flow Chart of the Experimental Procedure	
CHAPTER 4: DATA ANALYSISUniversity of Moratuwa, Sri Lanka.	44
4.1 Degree of Compactionivs. This tritial Moid Contentons	
CHAPTER 3. CONCLUSION .mrt.ac.lk	
CHAPTER 6: DISCUSSION	53
REFERENCES	56
APPENDICES	57
APPENDIX - A. Core Sample Data	58
APPENDIX - B. Core Sample Data in 12 Selected Locations - Road A	61
APPENDIX - C. Core Sample Data - After 100 Days - Road A	62
APPENDIX - D. Core Sample Data - After 225 Days - Road A	63
APPENDIX - E. Core Sample Data - After 2050 Days - Road B	64
APPENDIX - F. HMA Mix Design Report of Road A	65
APPENDIX - G. HMA Mix Design Report of Road B	79

LIST OF FIGURES

Figure 2-1: Composition of HMA	3
Figure 2-2: Laying of HMA (original in colour)	4
Figure 2-3: Volumetric phase diagram of a compacted HMA	5
Figure 2-4: Establishing a roller pattern using a test strip	. 14
Figure 2-5: HMA compaction (original in colour)	. 15
Figure 2-6: Initial compaction with the finisher	. 22
Figure 2-7: Static compaction	. 23
Figure 2-8: Compacting by pneumatic tired roller	. 23
Figure 2-9: Vibratory compaction.	. 23
Figure 2-10: Alligator cracking (original in colour)	. 25
Figure 2-11: Block cracking (original in colour)	. 25
Figure 2-12: Longitudinal (linear) cracking (original in colour)	. 26
Figure 2-13: Transverse cracking (original in colour)	. 26
Figure 2-14: Edge cracks (original in colour)	. 27
Figure 2-15 Joint reflection cracks (original in colour) Electronic Theses & Dissertations	. 27
Figure 2-16: Shippage cracks (original in colour)	. 28
Figure 2-17: Pot holes (original in colour)	
Figure 2-18: Depression (original in colour)	. 29
Figure 2-19: Rutting (original in colour)	. 30
Figure 2-20: Shoving (original in colour)	. 30
Figure 2-21: Raveling (original in colour)	. 31
Figure 2-22: Bleeding (original in colour)	. 31
Figure 3-1: Flow chart of the experimental procedure	. 37
Figure 3-2: Asphalt laying on top of the complete base course (original in colour)	. 38
Figure 3-3: Core sample taking before open to traffic (original in colour)	. 38
Figure 3-4: Obtain mass of dry completed sample (original in colour)	. 39
Figure 3-5: Place the core sample here (original in colour)	. 39
Figure 3-6: Obtain mass of the specimen in SSD condition (original in colour)	. 39
Figure 3-7: Core sample taking after 100 days and 225 days (original in colour)	. 40
Figure 3-8: Core locations of road A	.41

Figure 3-9: Laying of asphalt on a road which has HMA over lay 5 years before
(original in colour)
Figure 3-10: Asphalt laying records
Figure 3-11: Obtaining core samples from road B (original in colour)
Figure 3-12: Measuring the thickness of core sample (original in colour)43
Figure 4-1: Degree of compaction vs. percentage air voids – Data of both roads A&
B
Figure 4-2: Degree of compaction vary with the time - Road A
Figure 4-3: Degree of compaction vary with the time - Roads A and B together 46
Figure 4-4: Air void content vary with the time - Road A
Figure 4-5: Air void content vary with the time - Roads A and B together



LIST OF TABLES

Table 2-1: Effect of compaction of pavement performance (after R.N. Linde	n et al.)
	13
Table 3-1: Aggregate properties	34
Table 3-2: Aggregate grading, binder content, and thickness requirement	35
Table 3-3: Permissible variations from job mix formula	36
Table 4-1: Degree of compaction - Road A	45
Table 4-2: Degree of compaction - Roads A and B together	46
Table 4-3: Air void content - Road A	47
Table 4-4: Air void content - Roads A and B together	48
Table 4-5: Performance of road A after 100 days open to traffic	49
Table 4-6: Performance of the road 'A' after 225 days open to traffic	50
Table 4-7: Performance of road 'B' after 2050 days open to traffic	51



LIST OF ABBREVIATIONS

Wherever the following abbreviations of titles, terms, and units of measurement are used in the Specifications or on the Drawings, the intent and meaning shall be interpreted as described hereunder.

HMA- Hot Mix Asphalt

CMA- Cold Mix Asphalt

GTM- Gyratory Testing Machine

VFA- Voids Filled with Asphalt

VMA- Voids in the mineral aggregate

ESAL-Equivalent Single Axle Load

ASTM-American Society for Testing and Materials [an international standards organization that develops and publishese sofundary consensor technical standards] www.lib.mrt.ac.lk