

References and Bibliography

[01] S. K. Wang, “Handbook of Air Conditioning and Refrigeration”, 2nd ed, New York, McGraw-Hill, 2000, pp. 41.

[02] *IEEE Recommended Practice for Electric Power Systems in Commercial Buildings*, IEEE Std 241-1990.

[03] S. Cao et al., “An Innovation PID Control Method of Split Air-conditioner Based on Online Prediction”, in *International Conference on Electrical and Control Engineering*, Wuhan, 2010, pp. 400 – 403.

[04] Y. Tomita et al., “Energy Efficient Demand Control for Air-Conditioning Systems”, in *IEEE Power & Energy Society General Meeting*, Vancouver, BC, 2013, pp. 1 – 5.

[05] J. Xu et al., “Simulation Research on Optimal Control of Multi split Air Conditioning System”, in *Knowledge Acquisition and Modeling Workshop*, Wuhan, 2008, pp. 263 – 266.

[06] M. Tsay and C. Lin, “Application of Artificial Neural Network for Electrical Energy Management of Air-conditioning Systems”, in *IEEE Region 10 Conference on Computers, Communications, Control and Power Engineering*, 2002, pp. 1954 - 1957 vol.3.

[07] J. Wang et al., “Non-invasive Zigbee wireless controller for air conditioner energy saving”, in *7th International Conference on Wireless Communications, Networking and Mobile Computing (WiCOM)*, Wuhan, 2011, pp. 1 – 4.

[08] *XBee®/XBee-PRO® RF Modules Product Manual*, v1.xEx - 802.15.4 Protocol, Digi Int. Inc., Minnetonka, MN, 2009.

[09] *LM35 Precision Centigrade Temperature Sensor Datasheet*, Rev. D, Texas Instruments Inc., Dallas, TX, 2013.

[10] *Honeywell HIH-4030 Humidity Sensor Datasheet*, Honeywell International Inc., Minneapolis, MN, 2008.

[11] *DS1307 Real Time Clock IC Datasheet*, Maxim Integrated Products, Sunnyvale, CA, 2015.



[12] *LM317 Adjustable Regulator IC Datasheet*, Rev. W, Texas Instruments Inc., Dallas, TX, 2014.



[13] *SN74HC595 8-bit Shift Register Datasheet*, Rev. I, Texas Instruments Inc., Dallas, TX, 2015.



[14] *LM324 Low Power Quad Operational Amplifier Datasheet*, Rev. D, Texas Instruments Inc., Dallas, TX, 2015.


Appendix 01

Start time - 0850 Hrs and measured for 3500 s
















Start time - 1015 Hrs and measured for 4500 s
















Start time - 1240 Hrs and measured for 1600 s
















Start time - 1315 Hrs and measured for 1600 s
















Start time - 1400 Hrs and measured for 3500 s
















Start time - 1515 Hrs and measured for 2000 s
















Start time - 1610 Hrs and measured for 2500 s









Appendix 02

