

7. REFERENCES

- Adams, C.A., Zambang, M.A.M., & Opoku, R. (2015). Effects of motorcycles on saturation flow rates of mixed traffic at signalized intersection in Ghana, *International Journal of Traffic and Transportation Engineering*, 4(3), 94-101.
- Alam, M.J.B., Osra, K.A., Al-Bar, H.O., & Zahran, S.Z. (2011). Signalized intersection capacity adjustment factors for Makkah, Saudi Arabia. *Canadian Journal of Transportation*, 4(1).
- Bester, C.J., & Meyers, W.L. (2007). Saturation flow rates. *Proc. 26th Southern African Transport Conference*, Pretoria, South Africa.
- Bester, C.J., & Varndell, P.J., (2002). The effect of a leading green phase on the start-up lost time of opposing vehicles. *South African Transport Conference*, Pretoria, South Africa.
- Branston, D.M. (1977). Some factors affecting the capacity of signalized intersections. *Traffic Engineering and Control*, 20 (August/September), pp.390-396.
- Branston, D., & Gipps, P. (1981). Some experiences with a multiple regression method of estimating parameters at the traffic departure process. *Transportation Research*, 6A, pp. 445-458.
- Dunlap, B.M. (2005). *Field measurement of ideal saturation flow rate from the highway capacity manual*. Master Thesis, Department of Civil Eng., University of West Virginia, Morgantown, West Virginia.
- Greenshields. B.D., Shapiro, D., & Ericksen, E.L. (1947). *Traffic performances at urban intersections* (Technical Report No. 1). Bureau of Highway Traffic, Yale University.
- Hadiuzzaman, M., Rahman, M.M., & Karim, M.A. (2008). Saturation flow model at signalized intersection for non-lane based traffic. *Canadian Journal of Transportation* 2(1).

- Hamad, K., & Abuhamda, H. (2015). Estimating base saturation flow rate for selected signalized intersections in Doha, Qatar, *Journal of Traffic and Logistics Engineering* 3(1). Retrieved from <http://www.jtle.net/uploadfile/2015/0826/20150826021325831.pdf>
- Holroyd, E.M. (1963). Effect of motorcycles and pedal cycles on saturation flow at traffic signals. *Road and Road Construction*, 41, pp. 315-316.
- Hounsell, N.B. (1989). *The design and performance of signal controlled intersections*. Ph.D. thesis, Department of Civil Engineering, University of Southampton.
- Leong, L.V. (2004). *A study on saturation flow rates of through vehicles at signalized intersections based on Malaysian road conditions*. Ph.D. thesis, University of Sains, Malasia.
- Mukwaya, R., Mwesige, G. (2012). Saturation flow rate for through traffic at signalized junction in Kampala. *Proc. Second International Conference on Advances in Engineering and Technology*, Kampala, Uganda.
- Rahman, M.M., Ahmed S.N., & Hassan, T. (2005). Comparison of saturation flow rate at signalized intersection in Yokohama and Dhaka. *Proceeding of the Eastern Asia Society for Transportation Studies*. vol. 5, pp. 959-966.
- Shao, C.Q., Rong J., & Liu, X.M. (2011). Study on the saturation flow rate and its influence factors at signalized intersections at China, *Procedia Social and Behavioral Sciences* 16, 504-514. Retrieves from https://ac.els-cdn.com/S1877042811010172/1-s2.0-S1877042811010172-main.pdf?_tid=53586486-f517-11e7-aa8a00000aab0f02&acdnat=1515486799_bfae009677b38c890719832054ed3bbd
- Transport and Road Research Laboratory. (1963). *A Method of Measuring Saturation Flow at Traffic Signals*. Road Note No 34, London.
- Transportation Research Board. (2000). *Highway Capacity Manual 2000*. National Research Council, Washington, D.C.
- Transportation Research Board. (2016). *Highway Capacity Manual 2016*. National Research Council, Washington, D.C.

Tuner, J., & harahap, G. (1993). Simplified saturation flow data collection methods. Transport Research Laboratory, Crowthorne, pp. 1292-1293.