References

[1] E. H. Adelson and J. R. Bergen, "The plenoptic function and the elements of early vision," in *Computation Models of Visual Processing*, M. Landy and J. A. Movshon, Eds. Cambridge, MA: MIT Press, 1991, pp. 3–20.

[2] M. Levoy and P. Hanrahan, "Light field rendering," in *Proc. Annu. Conf. Comput. Graph. (SIGGRAPH)*, 1996, pp. 31–42.

[3] D. Dansereau and L. Bruton, "A 4D frequency-planar IIR filter and its application to light field processing," in *Proc. IEEE Int. Symp. Circuits Syst.*, vol. 4, 2003, pp. IV–476–IV–479.

[4] G. Wu, B. Masia, A. Jarabo, Y. Zhang, L. Wang, Q. Dai, T. Chai, and Y. Liu, "Light field image processing: An overview," *IEEE J. Sel. Topics Signal Process.*, vol. 11, no. 7, pp. 926–954, Oct. 2017.

[5] A. Madanayake, C. Wijenayake, D. G. Dansereau, T. K. Gunaratne, L. T. Bruton, and S. B. Williams, "Multidimensional (MD) circuits and systems for emerging applications including cognitive radio, radio astronomy, robot vision and imaging," *IEEE Circuits Syst. Mag.*, vol. 13, no. 1, pp. 10–43, 2013.

[6] R. Ng, M. Levoy, M. Brédif, G. Duval, M. Horowitz, and P. Hanrahan, "Light field photography with a hand-held plenoptic camera," Stanford Univ., Stanford, CA, Tech. Rep. CTSR 2005-02, 2005.

[7] O. Pizarro, S. B. Williams, M. V. Jakuba, M. Johnson-Roberson, I. Mahon, M. Bryson, D. Steinberg, A. Friedman, D. Dansereau, N. Nourani-Vatani *et al.*, "Benthic monitoring with robotic platforms—the experience of australia," in *Proc. IEEE Int. Symp. Underwater Technology.* IEEE, 2013, pp. 1–10.

[8] D. G. Dansereau, "Plenoptic signal processing for robust vision in field robotics," Ph.D. dissertation, 2014.

[9] D. G. Dansereau, O. Pizarro, and S. B. Williams, "Linear volumetric focus for light field cameras," *ACM Trans. Graph.*, vol. 34, no. 2, pp. 15:1–15:20, Feb. 2015.

[10] D. E. Dudgeon and R. M. Mersereau, *Multidimensional Digital Signal Processing.* Englewood Cliffs, NJ: Prentice-Hall, 1984.

[11] S. U. Premaratne, C. U. Edussooriya, C. Wijenayake, L. T. Bruton, and P. Agathoklis, "A 4-D sparse FIR hyperfan filter for volumetric refocusing of light fields by hard thresholding," in *Proc. IEEE Int. Conf. Digital Signal Process.* IEEE, 2018, pp. 1–5.

[12] D. G. Dansereau, D. L. Bongiorno, O. Pizarro, and S. B. Williams, "Light field image denoising using a linear 4D frequency-hyperfan all-in-focus filter," in *Proc. SPIE Comput. Imag. XI*, vol. 8657, 2013, pp. 86 570P–1–86 570P–14.

[13] L. McMillan and G. Bishop, "Plenoptic modeling: An image-based rendering system," in *Proceedings of the 22nd Annual Conference on Computer Graphics and Interactive Techniques.* ACM, 1995, pp. 39–46.

[14] C. Zhang and T. Chen, "A survey on image-based rendering—representation, sampling and compression," *Signal Process.: Image Commun.*, vol. 19, no. 1, pp. 1–28, Jan. 2004.

[15] H.-Y. Shum, S. B. Kang, and S.-C. Chan, "Survey of image-based representations and compression techniques," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 13, no. 11, pp. 1020–1037, Nov. 2003.

[16] C. U. S. Edussooriya, D. G. Dansereau, L. T. Bruton, and P. Agathoklis, "Five-dimensional depth-velocity filtering for enhancing moving objects in light field videos," *IEEE Trans. Signal Process.*, vol. 63, no. 8, pp. 2151–2163, Apr. 2015.

[17] E. H. Adelson and J. Y. Wang, "Single lens stereo with a plenoptic camera," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 14, no. 2, pp. 99–106, 1992.

[18] R. Ng, "Digital light field photography," Ph.D. dissertation, Stanford University, CA,USA, 2006.

[19] S. B. Kang, "Survey of image-based rendering techniques," in *Videometrics VI*, vol. 3641. International Society for Optics and Photonics, 1998, pp. 2–17.

[20] M. Levoy, "Light fields and computational imaging," *Computer*, vol. 39, no. 8, pp. 46–55, Aug 2006.

[21] A. Isaksen, L. McMillan, and S. J. Gortler, "Dynamically reparameterized light fields," in *Proc. Annu. Conf. Comput. Graph. (SIGGRAPH)*, 2000, pp. 297–306.

[22] D. Dansereau and L. T. Bruton, "A 4-D dual-fan filter bank for depth filtering in light fields," *IEEE Trans. Signal Process.*, vol. 55, no. 2, pp. 542–549, Feb. 2007.

[23] N. Liyanage, C. Wijenayake, C. U. S. Edussooriya, A. Madanayake, P. Agathoklis, E. Ambikairajah, and L. Bruton, "Low-complexity 4-D IIR filters for multi-depth filtering and occlusion suppression in light fields," in *Proc. IEEE Int. Symp. Circuits Syst.*, 2018, pp. 1–5.

[24] J. Yu, "A light-field journey to virtual reality," *IEEE MultiMedia*, vol. 24, no. 2, pp. 104–112, 2017.

[25] D. G. Dansereau, I. Mahon, O. Pizarro, and S. B. Williams, "Plenoptic flow: Closed-form visual odometry for light field cameras," in *Proc. IEEE/RSJ Int. Conf. Intell. Robot. Syst.*, 2011, pp. 4455–4462.

[26] F. Dong, S.-H. Ieng, X. Savatier, R. Etienne-Cummings, and R. Benosman, "Plenoptic cameras in real-time robotics," *The International Journal of Robotics Research*, vol. 32, no. 2, pp. 206–217, 2013.

[27] N. Zeller, F. Quint, and U. Stilla, "From the calibration of a light-field camera to direct plenoptic odometry," *IEEE J. Sel. Topics Signal Process.*, vol. 11, no. 7, pp. 1004–1019, 2017.

[28] M. Lingenauber, K. H. Strobl, N. W. Oumer, and S. Kriegel, "Benefits of plenoptic cameras for robot vision during close range on-orbit servicing maneuvers," in *IEEE Conf. Aerosp.* IEEE, 2017, pp. 1–18.

[29] S. Hasirlioglu, M. Karthik, A. Riener, and I. Doric, "Potential of plenoptic cameras in the field of automotive safety," in *First International Conference on Intelligent Transport Systems.* Springer, 2017, pp. 164–173.

[30] A. Sepas-Moghaddam, F. Pereira, and P. L. Correia, "Ear recognition in a light field imaging framework: A new perspective," *IET Biometrics*, vol. 7, no. 3, pp. 224–231, 2018.

[31] S. Shi, J. Wang, J. Ding, Z. Zhao, and T. New, "Parametric study on light field volumetric particle image velocimetry," *Flow Measurement and Instrumentation*, vol. 49, pp. 70–88, 2016.

[32] A. Sepas-Moghaddam, F. Pereira, and P. L. Correia, "Light field-based face presentation attack detection: reviewing, benchmarking and one step further," *IEEE Trans. Inf. Forens. Security*, vol. 13, no. 7, pp. 1696–1709, 2018.

[33] X. Zhou, "Sampling models in light fields," Ph.D. dissertation, École Polytechnique Fédérale de Lausanne, 2016.

[34] Lytro Inc. [Online]. Available: https://www.lytro.com/

[35] ——. [Online]. Available: https://www.lytro.com/illum/

[36] Raytrix GmbH. [Online]. Available: https://www.raytrix.de/

[37] M. Levoy. (2002) The stanford multi-camera array. [Online]. Available: http://graphics.stanford.edu/projects/array/

[38] B. Wilburn, N. Joshi, V. Vaish, E.-V. Talvala, E. Antunez, A. Barth, A. Adams, M. Horowitz, and M. Levoy, "High performance imaging using large camera arrays," in *Proc. Annu. Conf. Comput. Graph. (SIGGRAPH)*, 2005, pp. 765–776.

[39] M. Levoy. (2005) Stanford light field microscope project. [Online]. Available: http://graphics.stanford.edu/projects/lfmicroscope/

[40] ——. (2004) Stanford spherical gantry. [Online]. Available: https://graphics.stanford.edu/projects/gantry/

[41] K. Venkataraman, D. Lelescu, J. Duparré, A. McMahon, G. Molina, P. Chatterjee, R. Mullis, and S. Nayar, "PiCam: An ultra-thin high performance monolithic camera array," *ACM Trans. Graph.*, vol. 32, no. 6, pp. 166:1–166:13, Nov. 2013.

[42] A. J. Theuwissen, "CMOS image sensors: State-of-the-art," *Solid-State Electronics*, vol. 52, no. 9, pp. 1401–1406, 2008.

[43] H. Tian, "Noise analysis in CMOS image sensors," Ph.D. dissertation, Department of Applied Physics, Stanford University, CA,USA, 2000.

[44] J. Nakamura, *Image Sensors and Signal Processing for Digital Still Cameras.* CRC press, 2016.

[45] P. Jain and V. Tyagi, "A survey of edge-preserving image denoising methods," *Information Systems Frontiers*, vol. 18, no. 1, pp. 159–170, 2016.

[46] L. Shao, R. Yan, X. Li, and Y. Liu, "From heuristic optimization to dictionary learning: A review and comprehensive comparison of image denoising algorithms," *IEEE Trans. Cybern.*, vol. 44, no. 7, pp. 1001–1013, 2014.

[47] K. Dabov, A. Foi, V. Katkovnik, and K. Egiazarian, "Image denoising by sparse 3-D transform-domain collaborative filtering," *IEEE Trans. Image Process.*, vol. 16, no. 8, pp. 2080–2095, 2007.

[48] A. Beck and M. Teboulle, "Fast gradient-based algorithms for constrained total variation image denoising and deblurring problems," *IEEE Transactions on Image Processing*, vol. 18, no. 11, pp. 2419–2434, 2009.

[49] M. Elad and M. Aharon, "Image denoising via sparse and redundant representations over learned dictionaries," *IEEE Trans. Image Process.*, vol. 15, no. 12, pp. 3736–3745, 2006.

[50] K. Dabov, A. Foi, and K. Egiazarian, "Video denoising by sparse 3D transform-domain collaborative filtering," in *2007 15th European Signal Processing Conference*, Sep. 2007, pp. 145–149.

[51] M. Maggioni, G. Boracchi, A. Foi, and K. Egiazarian, "Video denoising, deblocking, and enhancement through separable 4-D nonlocal spatiotemporal transforms," *IEEE Trans. Image Process*, vol. 21, no. 9, pp. 3952–3966, 2012.

[52] Z. Li, H. Baker, and R. Bajcsy, "Joint image denoising using light-field data," in *IEEE Int. Conf. Multimedia and Expo Workshops.* IEEE, 2013, pp. 1–6.

[53] A. Sepas-Moghaddam, P. L. Correia, and F. Pereira, "Light field denoising: exploiting the redundancy of an epipolar sequence representation," in *Proc. IEEE 3DTV Conf.* IEEE, 2016, pp. 1–4.

[54] M. Alain and A. Smolic, "Light field denoising by sparse 5D transform domain collaborative filtering," in *IEEE Int. Workshop on Multimedia Signal Process. (MMSP).* IEEE, 2017, pp. 1–6.

[55] J. Chen, J. Hou, and L.-P. Chau, "Light field denoising via anisotropic parallax analysis in a CNN framework," *arXiv preprint arXiv:1805.12358*, 2018.

[56] P. Allain, L. Guillo, and C. Guillemot, "Light field denoising using 4d anisotropic diffusion," in *IEEE Int. Conf. Acoust., Speech, Signal Process. (ICASSP).* IEEE, 2019, pp. 1692–1696.

[57] A. Bajpayee, A. H. Techet, and H. Singh, "Real-time light field processing for autonomous robotics," in *IEEE/RSJ Int. Conf. Intell. Robot. Syst.* IEEE, 2018, pp. 4218–4225.

[58] N. Wadhwa, R. Garg, D. E. Jacobs, B. E. Feldman, N. Kanazawa, R. Carroll, Y. Movshovitz-Attias, J. T. Barron, Y. Pritch, and M. Levoy, "Synthetic depth-of-field with a single-camera mobile phone," *ACM Trans. Graph.*, vol. 37, no. 4, p. 64, 2018.

[59] L. Wang, X. Shen, J. Zhang, O. Wang, Z. Lin, C.-Y. Hsieh, S. Kong, and H. Lu, "Deeplens: shallow depth of field from a single image," *arXiv preprint arXiv:1810.08100*, 2018.

[60] R. Ng, "Fourier slice photography," in *Proc. Annu. Conf. Comput. Graph. (SIGGRAPH)*, 2005, pp. 735–744.

[61] J. Fiss, B. Curless, and R. Szeliski, "Refocusing plenoptic images using depth-adaptive splatting," in *Proc. Int. Conf. Comput. Photogr.*, 2014, pp. 1–9.

[62] M. Rerabek and T. Ebrahimi. (2016) New light field image dataset. [Online]. Available: http://mmspg.epfl.ch/EPFL-light-field-image-dataset

[63] R. Szeliski, *Computer Vision: Algorithms and Applications.* London: Springer, 2011.

[64] K. J. Dana, B. Van Ginneken, S. K. Nayar, and J. J. Koenderink, "Reflectance and texture of real-world surfaces," *ACM Trans. Graph.*, vol. 18, no. 1, pp. 1–34, 1999.

[65] D. G. Dansereau, "4D light field processing and its application to computer vision," Master's thesis, AB, Canada, 2003.

[66] R. C. Bolles, H. H. Baker, and D. H. Marimont, "Epipolar-plane image analysis: An approach to determining structure from motion," *Int. J. Comput. Vision*, vol. 1, no. 1, pp. 7–55, 1987.

[67] C. U. S. Edussooriya, "Low-complexity multi-dimensional filters for plenoptic signal processing," Ph.D. dissertation, Department of Electrical and Computer Engineering, University of Victoria, Victoria, BC, Canada, 2015.

[68] J.-X. Chai, X. Tong, S.-C. Chan, and H.-Y. Shum, "Plenoptic sampling," in *Proc. Annu. Conf. Comput. Graph. (SIGGRAPH)*, 2000, pp. 307–318.

[69] A. Levin, S. W. Hasinoff, P. Green, F. Durand, and W. T. Freeman, "4D frequency analysis of computational cameras for depth of field extension," in *Proc. Annu. Conf. Comput. Graph. (SIGGRAPH)*, 2009, pp. 97:1–97:14.

[70] M. Rerabek and T. Ebrahimi, "New light field image dataset," in *Proc. 8th Int. Conf. Quality Multimedia Experience*, 2016, pp. 1–2. [Online]. Available: http://mmspg.epfl.ch/EPFL-light-field-image-dataset

[71] Computer Graphics Laboratory, Stanford University. (2008) The (New) Stanford Light Field Archive. [Online]. Available: http://lightfield.stanford.edu/lfs.html

[72] Y. Liu, N. Qi, Z. Cheng, D. Liu, Q. Ling, and Z. Xiong, "Tensor-based light field denoising by integrating super-resolution," in *IEEE Int. Conf. Image Process. (ICIP)*. IEEE, 2018, pp. 3209–3213.

[73] S. Fujita, K. Takahashi, and T. Fujii, "How should we handle 4d light fields with cnns?" in *IEEE Int. Conf. Image Process (ICIP)*, Oct 2018, pp. 2600–2604.

[74] L. Khademi and L. T. Bruton, "Reducing the computational complexity of narrowband 2D fan filters using shaped 2D window functions," in *Proc. IEEE Int. Symp. Circuits Syst.*, vol. 3, 2003, pp. III–702–III–705.

[75] R. T. Wijesekara, C. U. S. Edussooriya, L. T. Bruton, and P. Agathoklis, "A low-complexity 2-D spatially-interpolated FIR trapezoidal filter for enhancing broadband plane waves," in *Proc. IEEE Int. Workshop Multidim. Syst.*, 2017, pp. 1–6.

[76] ——, "A 3-D sparse FIR frustum filter for enhancing broadband plane waves," *IEEE Trans. Circuits Syst. II*, pp. 1–5, 2018.

[77] S.-C. Pei and S.-B. Jaw, "Two-dimensional general fan-type FIR digital filter design," *Signal Process.*, vol. 37, no. 2, pp. 265–274, May 1994.

[78] W.-S. Lu and A. Antoniou, *Two-Dimensional Digital Filters.* NY: Marcel Dekker, 1992.

[79] R. E. Blahut, *Fast Algorithms for Signal Processing.* NY: Cambridge University Press, 2010.

[80] C. U. S. Edussooriya, L. T. Bruton, and P. Agathoklis, "A novel 5-D depth–velocity filter for enhancing noisy light field videos," *Multidimensional Systems and Signal Processing*, vol. 28, no. 1, pp. 353–369, 2017.

[81] J. W. Woods, *Multidimensional Signal, Image, and Video Processing and Coding.* Elsevier, 2006.