

BIBLIOGRAPHY

- [01] https://www.european-coatings.com/var/StorageVincentz/VN-Link/547_Leseprobe.pdf
- [02] Hong N, Zhang S, Yi C, Xueqing Q. Effect of Polycarboxylic Acid Used as High-Performance Dispersant on Low Rank Coal-Water Slurry. *Journal of Dispersion Science and Technology*, 37, 2015, 415-422.
- [03] Penkavova V, Guerreiro M, Tihan J, Teixeira JAC. Deflocculation of kaolin suspensions – The effect of various electrolytes. *Applied Rheology*, 2015, 25, 24151-24165.
- [04] Hong N, Zhang S, Yi C, Xueqing Q. Effect of Polycarboxylic Acid Used as High-Performance Dispersant on Low Rank Coal-Water Slurry. *Journal of Dispersion Science and Technology*, 37, 2015, 415-422.
- [05] M. Pidwirny, Carbon Cycle, 2012. <http://www.eoearth.org/view/article/150923> (accessed date January 2015)
- [06] Department of Geology, Maryland University, Carbonate Sediments and Chemistry.<http://www.geol.umd.edu/jmerck/geol342/lectures/14.html> (accessed date January 2015).
- [07] R.L. Folk, Practical petrographic classification of limestones, *AAPG Bull.* 43 (1959) 1–38.
- [08] A.V. Radha, T.Z. Forbes, C.E. Illian, P.U.P.A. Gilbert, A. Navrotksy, Transformation and crystallization energetics of synthetic and biogenic amorphous calcium carbonate, *Proc. Natl. Acad. Sci. U.S.A.* 107 (2010) 16438–16443.
- [09] C. Peng, Q. Zhao, C. Gao, Sustained delivery of doxorubicin by porous CaCO_3 and chitosan/alginate multilayers-coated CaCO_3 microparticles, *Colloids Surf. A* 353 (2010) 132–139.
- [10] F. Liu, Y. Gao, S. Zhao, Q. Shen, Y. Su, D. Wang, Biomimetic fabrication of pseudohexagonal aragonite tablets through a temperature-varying approach, *Chem. Commun.* 46 (2010) 4607–4609.
- [11] B. Shany, H. Peretz, P. Blinder, Y. Lichtenfeld, R. Jeger, R. Vago, D. Baranes, Aragonite crystalline biomatrices support astrocytic tissue formation in vitro and in vivo, *Tissue Eng.* 12 (2006) 1763–1773.
- [12] L. Brec'evic', D. Kralj, On calcium carbonates: from fundamental research to application, *Croat. Chem. Acta* 80 (2007) 467–484.

- [13] T. Beuvier, B. Calvignac, G.J.-R. Delcroix, M.K. Tran, S. Kodjikian, N. Delorme, J.-F. Bardeau, A. Gibauda, F. Bour, Synthesis of hollow vaterite CaCO_3 micro-spheres in supercritical carbon dioxide medium, *J. Mater. Chem.* 21 (2011) 9757–9761.
- [14]. Charles Xu and Michael Paleologou, Production of Flocculants, Adsorbents, and Dispersants from Lignin, 10 April 2018.
- [15] D. Yang, H. Li, Y. Qin, R. Zhong, M. Bai, X. Qiu, Structure and properties of sodium lignosulfonate with different molecular weight used as dye dispersant, *J. Disper. Sci. Technol.* 36 (4) (2015) 532–539, <https://doi.org/10.1080/01932691.2014.916221>.
- [16] A. Vishtal, A. Kraslawski, Challenges in industrial applications of technical lignins, *BioResources* 6 (3) (2011) 3547–3568.
- [17] [93] F. Oveissi, P. Fatehi, Characterization of four different lignins as a first step toward the identification of suitable end-use applications, *J. Appl. Polym. Sci.* 132 (32) (2015) 1–9, <https://doi.org/10.1002/app.42336>.
- [18] A. Tejado, C. Peña, J. Labidi, J. Echeverria, I. Mondragon, Physico-chemical characterization of lignins from different sources for use in phenol-formaldehyde resin synthesis, *Bioresour. Technol.* 98 (8) (2007) 1655–1663, <https://doi.org/10.1016/j.biortech.2006.05.042>.
- [19] G. Shulga, V. Shakels, S. Skudra, V. Bogdanovs, Modified lignin as an environmentally friendly surfactant, *Environment Technology Resources, Proceedings of The International Scientific and Practical Conference*, 1 (2011) 276. [10.17770/etr2011vol1.919](https://doi.org/10.17770/etr2011vol1.919).
- [20] Ma M. The dispersive effect of sodium silicate on kaolinite particles in process water: Implications for iron ore processing. *Clay and Clay Minerals*, 2011, 59, 233-239.
- [21] Ece OI, Alemdar A, Gungor N, Hayashi S. Influence of non-ionic poly(ethylene glycol) polymer PEG on electrokinetic and rheological properties of bentonite suspensions. *Journal of Applied Polymer Science*, 2002, 86, 341-346.
- [22] Zhou M, Huang K, Yang D, Qiu X. Development and evaluation of polycarboxylic acid hyper-dispersant used to prepare high-concentrated coal-water slurry. *Powder Technology*. 2012, 229, 185-190.
- [23] Nasser, M.S., James, A.E., 2007. Effect of polyacrylamide polymers on floc size and rheological behaviour of kaolinite suspensions. *Colloids and Surfaces a-Physicochemical and Engineering Aspects* 301, 311-322.
- [24] Barnes, H.A., 1999. The yield stress—a review or ‘παντα ρει’—everything flows? *J. Non-Newtonian Fluid Mech.* 81, 133-178.

- [25] Klimpel, R.R., 1999. The selection of wet grinding chemical additives based on slurry rheology control. *Powder Technol.* 105, 430-435.
- [26] Hunter, R.J., 2000. Foundations of colloid science. Oxford University Press, Oxford
- [26]. Gustafsson, J. (2003) The effect of pH and electrolyte concentration on the dispersion properties of titanium dioxide, PhD Thesis, Åbo Akademi, Turku, 1-13.
- [27]. Sharma, B.R.; Dhuldhoya, N.C.; Merchant, U.C. Flocculants-an ecofriendly approach. *J. Polym. Environ.* **2006**, 14, 195–202. [Google Scholar] [CrossRef]
- [28]. Stepkowska, E.T., Perez-Rodriguez, J.L., Sayagues, M.J., Martinez-Blanes, J.M., 2003. Calcite,vaterite and aragonite forming on cement hydration from liquid and gaseous phase. *J. Therm. Anal. Calorim.* 73, 247–269.
- [29]. Lorusso, M. (2003) Optimisation of calcium carbonate for fillers in woodfree applications, Wood Pulp and Paper International Conference, Proceedings, Bratislava, pp.76-81.
- [30]. Ghosh, T. (1998) Rheology of kaolin-based pigment slurries and the coating colors they form: Part 1, *Tappi J.*, 81(5), 89-92.
- [31]. Dongkang, F., Shaozu, W., Xiaojia, H., Jinren, N. (2008) Preparation and property analysis of polyacrylate dispersant for calcium carbonate, *Colloids and Surfaces A: Physicochem. Eng. Aspects* 326, 122-128.
- [32]. Emmi Kallio, Petteri Paananen, Jari Käyhkö. The effect of anionicity and feed strategy on filler retention and agglomeration
- [33]. Brumbach, M.; Carty, W.M. Dispersant demand curves: Effect of PAA on the viscosity of several clays. *Ceram. Eng. Sci. Proc.* **2003**, 24, 183.
- [34]. Papo, A.; Piani, L.; Ricceri, R. Sodium tripolyphosphate and polyphosphate as dispersing agents for kaolin suspensions: Rheological characterization. *Colloids Surf. A Physicochem. Eng. Asp.* **2002**, 201, 219–230. [Google Scholar] [CrossRef]
- [35]. Qin, Y.; Yang, D.; Gu, F.; Li, X.; Xiong, W.; Zhu, J.Y. Biorefinery lignosulfonates as a dispersant for coal water slurry. *Sustain. Chem. Process.* **2016**, 4, 5. [Google Scholar] [CrossRef]
- [36]. A. Vishtal, A. Kraslawski, Challenges in industrial applications of technical lignins, *BioResources* 6 (3) (2011) 3547–3568.
- [37]. D. Watkins, M. Nuruddin, M. Hosur, A. Tcherbi-Narteh, S. Jeelani, Extraction and characterization of lignin from different biomass resources, *J. Mater. Res. Technol.* 4 (1) (2015) 26–32, <https://doi.org/10.1016/j.jmrt.2014.10.009>.

- [38]. Tejado, A., Pena, C., Labidi, J., Echeverria, J., and Mondragon, I. (2007) Bioresour. Technol., 98: 1655–1663.
- [39] L. Torres, A. Moctezuma, J. Avendaño, A. Muñoz, J. Gracida, Comparison of bio- and synthetic surfactants for EOR, J. Pet. Sci. Eng. 76 (1–2) (2011) 6–11, <https://doi.org/10.1016/j.petrol.2010.11.022>.
- [40]. Li, R.; Yang, D.; Guo, W.; Qiu, X. The adsorption and dispersing mechanisms of sodium lignosulfonate on Al₂O₃ particles in aqueous solution. Holzforschung 2013, 67, 387–394. [Google Scholar] [CrossRef]
- [41]. Ji, X.; Dong, Y.; Yuan, B.; Li, B.; Guo, M. Influence of glutaraldehyde on the performance of a lignosulfonate/chitosan-based medium density fiberboard adhesive. J. Appl. Polym. Sci. 2018, 135, 45870. [Google Scholar] [CrossRef]
- [42]. Sudarmoyo, Boni Swadesi, Aulia Novi Andini, Septoratno Siregar, Rani Kurnia, Ari Buhari, and I. G. S. Budiaman, Laboratory study: The development of a sodium lignosulfonate (SLS) surfactant formulation for light oil reservoir to improve oil recovery Published Online: 26 June 2018
- [43]. S. Sriram, B. Christopher, J. Lu, K.D. Hoon, W. Upali, A.P. Gary, Improved Oil Recovery Symposium, Tulsa, USA, 2012 (SPE, Tulsa 2012), SPE 154262.
- [44]. L.L. Schramm, Surfactants Fundamentals and Applications in the Petroleum Industry (The Press Syndicate of The University of Cambridge, United Kingdom, 2000).
- [45]. A. Toledo, A. García, I. Mondragon, J. Labidi, Lignin separation and fractionation by ultrafiltration, Sep. Purif. Technol. 71 (1) (2010) 38–43, <https://doi.org/10.1016/j.seppur.2009.10.024>.
- [46]. F. Oveissi, P. Fatehi, Characterization of four different lignins as a first step toward the identification of suitable end-use applications, J. Appl. Polym. Sci. 132 (32) (2015) 1–9, <https://doi.org/10.1002/app.42336>.
- [47] L. Tolosa, A. Rodríguez-Malaver, A. González, O. Rojas, Effect of Fenton's reagent on O/W emulsions stabilized by black liquor, J. Colloid Interface Sci. 294 (1) (2006) 182–186, <https://doi.org/10.1016/j.jcis.2005.06.09>
- [48]. J. Sheng, Status of surfactant EOR technology, Petroleum 1 (2) (2015) 97–105, <https://doi.org/10.1016/j.petlm.2015.07.003>
- [49]. G. Shulga, V. Shakels, S. Skudra, V. Bogdanovs, Modified lignin as an environmentally friendly surfactant, Environment Technology Resources, Proceedings of The International Scientific and Practical Conference, 1 (2011) 276. 10.17770/etr2011vol1.919.

[50]. Detroit, J. Lignin Dispersing Agent. U.S. Patent No. 3726, 17 January 2012. [Google Scholar]

[51]. W.S. Perkins, Surfactants: a primer. An in-depth discussion of the behavior of common types of surfactants, in: Dyeing, Printing and Finishing, ATI-Atlanta, 1998, pp. 51–54.

[52].https://www.munzing.com/fileadmin/templates/_media/downloads/technical-information/dispersing-agents/Dispersing-Technologies-MUNZING-2016.pdf

[53].Papo, A.; Piani, L.; Ricceri, R. Sodium tripolyphosphate and polyphosphate as dispersing agents for kaolin suspensions: Rheological characterization. *Colloids Surf. A Physicochem. Eng. Asp.* 2002, 201, 219–230. [Google Scholar] [CrossRef]

[54]. Gliese, T. (2006) Dispersants for fillers and coating pigments, *Wochenblatt für Papierfabrikation*, 134(22), 1314-1319.

[55]. K.A. Elraies, I.M. Tan, The Application of a new polymeric surfactant for chemical EOR, in: L. Romero-Zerón (Ed.), *Introduction to Enhanced Oil Recovery (EOR) Processes and Bioremediation of Oil-Contaminated Sites*, Chapter 2, InTech, 2012, doi: 10.5772/47975.

[56].S. Hong, J. Bae, G. Lewis, An evaluation of lignosulfonate as a sacrificial adsorbate in surfactant flooding, *SPE Reserv. Eng.* 2 (1) (1987) 17–27, <https://doi.org/10.2118/12699-pa>

[57]. C. Chen, M. Li, Y. Wu, R. Sun, Modification of lignin with dodecyl glycidyl ether and chlorosulfonic acid for preparation of anionic surfactant, *RSC Adv.* 4 (33) (2014) 16944–16950, <https://doi.org/10.1039/c4ra01873g>.

[58]. Konduri, M.K.; Fatehi, P. Adsorption and dispersion performance of oxidized sulfomethylated kraft lignin in coal water slurry. *Fuel Process. Technol.* 2018; in press. [Google Scholar]

[59]. He, W.; Fatehi, P. Preparation of sulfomethylated softwood kraft lignin as a dispersant for cement admixture. *RSC Adv.* 2015, 58, 47031–47039. [Google Scholar] [CrossRef]