

REFERENCES

- [1]. Danewalia,S,Sharma, G.,Thakur, S., & Singh, K. (2016). Agricultural wastes as a resource of raw materials for developing low-dielectric glass-ceramics. *Scientific Reports*, 6, 1–12. <https://doi.org/10.1038/srep24617>
- [2]. McKendry, P. (2002). McKendry, P.: Energy production from biomass (Part 1): Overview of biomass. *Bioresour. Technol.* 83, 37-46. *Bioresource Technology*, 83, 37–46. [https://doi.org/10.1016/S0960-8524\(01\)00118-3](https://doi.org/10.1016/S0960-8524(01)00118-3)
- [3]. Gudka, B., Jones, J. M., Lea-Langton, A. R., Williams, A., & Saddawi, A. (2016). A review of the mitigation of deposition and emission problems during biomass combustion through washing pre-treatment. *Journal of the Energy Institute*, 89(2), 159–171. <https://doi.org/10.1016/j.joei.2015.02.007>
- [4]. Korotkova T. G, Ksandopulo S. J, Donenko A. P, Bushumov S. A, Danilchenko A. S. Physical Properties and Chemical Composition of the Rice Husk and Dust. *OrientJChem* 2016;32(6). Available from: <http://www.orientjchem.org/?p=26245>
- [5]. Carrillo, M. A., Staggenborg, S. A., & Pineda, J. A. (2014). Washing sorghum biomass with water to improve its quality for combustion. *Fuel*, 116, 427–431. <https://doi.org/10.1016/j.fuel.2013.08.028>
- [6]. Bryers, R. W. (1996). Fireside slagging, fouling, and high-temperature corrosion of heat-transfer surface due to impurities in steam-raising fuels. *Progress in Energy and Combustion Science*, 22(1), 29–120. [https://doi.org/https://doi.org/10.1016/0360-1285\(95\)00012-7](https://doi.org/https://doi.org/10.1016/0360-1285(95)00012-7)
- [7]. Jenkins, B. M., Baxter, L. L., Miles, T. R., & Miles, T. R. (1998). Combustion properties of biomass. *Fuel Processing Technology*, 54(1), 17–46. [https://doi.org/https://doi.org/10.1016/S0378-3820\(97\)00059-3](https://doi.org/https://doi.org/10.1016/S0378-3820(97)00059-3)
- [8]. Miles, T. R., Miles, T. R., Baxter, L. L., Bryers, R. W., Jenkins, B. M., & Oden, L. L. (1996). Boiler deposits from firing biomass fuels. *Biomass and Bioenergy*, 10(2), 125–138. [https://doi.org/https://doi.org/10.1016/0961-9534\(95\)00067-4](https://doi.org/https://doi.org/10.1016/0961-9534(95)00067-4)

- [9]. Heinzel, T., Siegle, V., Spliethoff, H., & Hein, K. R. G. (1998). Investigation of slagging in pulverized fuel co-combustion of biomass and coal at a pilot-scale test facility. *Fuel Processing Technology*, 54(1), 109–125.
[https://doi.org/https://doi.org/10.1016/S0378-3820\(97\)00063-5](https://doi.org/https://doi.org/10.1016/S0378-3820(97)00063-5)
- [10]. Nutalapati, D., Gupta, R., Moghtaderi, B., & Wall, T. F. (2007). Assessing slagging and fouling during biomass combustion: A thermodynamic approach allowing for alkali/ash reactions. *Fuel Processing Technology*, 88(11), 1044–1052.
<https://doi.org/https://doi.org/10.1016/j.fuproc.2007.06.022>
- [11]. Kostakis, G. (2010). Mineralogical composition of boiler fouling and slagging deposits and their relation to fly ashes: The case of Kardia power plant. *Journal of Hazardous Materials*, 185, 1012–1018.
<https://doi.org/10.1016/j.jhazmat.2010.10.006>
- [12]. Benson, S.A., (U.S.), E. F., & Center, B. Y. U. A. C. E. R. (1992). Inorganic transformations and ash deposition during combustion: proceedings of the Engineering Foundation Conference on Inorganic Transformations and Ash Deposition During Combustion, March 10-15, 1991, in Palm Coast, Florida. Retrieved from <https://books.google.lk/books>
- [13]. Zevenhoven, M., Yrjas, P., Skrifvars, B. J., & Hupa, M. (2012). Characterization of ash-forming matter in various solid fuels by selective leaching and its implications for fluidized-bed combustion. *Energy and Fuels*, 26(10), 6366–6386.
<https://doi.org/10.1021/ef300621j>
- [14]. Davidsson, K. O., Korsgren, J. G., Pettersson, J. B. C., & Jäglid, U. (2002). The effects of fuel washing techniques on alkali release from biomass. *Fuel*, 81(2), 137–142. [https://doi.org/https://doi.org/10.1016/S0016-2361\(01\)00132-6](https://doi.org/https://doi.org/10.1016/S0016-2361(01)00132-6)
- [15]. Huanpeng, L. et al., 2013. The effects of leaching methods on the combustion characteristics of rice straw. *Biomass and Energy*, pp. 22-27.
- [16]. Runge, T., Wipperfurth, P., & Zhang, C. (2013). Improving biomass combustion quality using a liquid hot water treatment. *Biofuels*, 4, 73–83. <https://doi.org/10.4155/bfs.12.70>
- [17]. Patel, M. (1987). Effect of thermal and chemical treatments on carbon and silica in rice husk. *J. Material Science*, 22, 2457–2464.

- [18]. Armesto, L., Bahillo, A., Veijonen, K., Cabanillas, A., & Otero, J. (2002). Combustion behaviour of rice husk in a bubbling fluidised bed. *Biomass and Bioenergy*, 23(3), 171–179. [https://doi.org/https://doi.org/10.1016/S0961-9534\(02\)00046-6](https://doi.org/https://doi.org/10.1016/S0961-9534(02)00046-6)
- [19]. Archibald, John Geddie, "The effect of sodium hydroxide on the composition, digestibility and feeding value of grain hulls and other fibrous material" (1924). Retrieved from <https://scholarworks.umass.edu/theses/1287>.
- [20]. Hsieh, Y., Du, Y., Jin, F., Zhou, Z., & Enomoto, H. (2009). Alkaline pre-treatment of rice hulls for hydrothermal production of acetic acid. *Chemical Engineering Research and Design*, 87(1), 13–18. <https://doi.org/https://doi.org/10.1016/j.cherd.2008.07.001>
- [21]. Deng, L., Zhang, T., & Che, D. (2013). Effect of water washing on fuel properties, pyrolysis and combustion characteristics, and ash fusibility of biomass. *Fuel Processing Technology*, 106, 712–720. <https://doi.org/10.1016/j.fuproc.2012.10.006>
- [22]. Zevenhoven, M., Yrjas, P., Skrifvars, B.-J., & Hupa, M. (2012). Characterization of Ash-Forming Matter in Various Solid Fuels by Selective Leaching and Its Implications for Fluidized-Bed Combustion. *Energy & Fuels*, 26, 6366–6386. <https://doi.org/10.1021/ef300621j>
- [23]. Jenkins, B. M., Bakker, R. R., & Wei, J. B. (1996). On the properties of washed straw. *Biomass and Bioenergy*, 10(4), 177–200.
- [24]. Jenkins, B. M., Mannapperuma, J. D., & Bakker, R. R. (2003). Biomass leachate treatment by reverse osmosis. *Fuel Processing Technology*, 81(3), 223–246. [https://doi.org/https://doi.org/10.1016/S0378-3820\(03\)00010-9](https://doi.org/https://doi.org/10.1016/S0378-3820(03)00010-9)
- [25]. Das, P., Ganesh, A., & Wangikar, P. (2004). Influence of pretreatment for deashing of sugarcane bagasse on pyrolysis products. *Biomass and Bioenergy*, 27(5), 445–457. <https://doi.org/https://doi.org/10.1016/j.biombioe.2004.04.002>
- [26]. Dilute Ammonia Pretreatment of Sorghum and Its Effectiveness on Enzyme Hydrolysis and Ethanol Fermentation Applied Biochemistry and Biotechnology, 2010, Volume 161, Number 1-8, Page67Deepti A. Salvi, Giovanna M. Aita, Diana Robert, Show All (4)

- [27]. Frank Hensgen, Michael Wachendorf Energies 2018, 11(4), 846; <https://doi.org/10.3390/en11040846>
Article Aqueous Leaching Prior to Dewatering Improves the Quality of Solid Fuels from Grasslands
- [28]. Lam, P. Y., Lim, C. J., Sokhansanj, S., Lam, P. S., Stephen, J. D., Pribowo, A., & Mabee, W. E. (2014a). Leaching characteristics of inorganic constituents from oil palm residues by water. *Industrial and Engineering Chemistry Research*, 53(29), 11822–11827. <https://doi.org/10.1021/ie500769s>
- [29]. Engineering, P., & Kong, Z. (2014). School of Science and Engineering Department of Chemical & Petroleum Engineering Effects of Pyrolysis Conditions and Biomass Properties on Leachability and Recyclability of Inorganic Nutrients in Biochars Produced from Mallee Biomass Pyrolysis Zhaoying Ko. (August).
- [30]. Kong, Z., Liaw, S. B., Gao, X., Yu, Y., & Wu, H. (2014). Leaching characteristics of inherent inorganic nutrients in biochars from the slow and fast pyrolysis of mallee biomass. *Fuel*, 128, 433–441. <https://doi.org/10.1016/j.fuel.2014.03.025>
- [31]. Zhang, S., Dong, Q., Zhang, L., Xiong, Y., Liu, X., Zhu, S. (2015). Effects of water washing and torrefaction pretreatments on rice husk pyrolysis by microwave heating, Bioresour. Technol. 193, 442-448.
<https://doi.org/10.1016/j.biortech.2015.06.142>