

REFERENCES

- 1) Ellinwa AU, Mahmood YA. Ash from timber waste as cement replacement. *Cement Concr Compos* 2002; 24:219–22.
- 2) Udoeyo FF, Dashibil PU. Sawdust ash as concrete material. *J Mater Civ Eng* 2002; 14(2):173–6.
- 3) Udoeyo FF, Inyang H, Young DT, Oparadu EE. Potential of wood ash waste as an additive in concrete. *J Mater Civ Eng* 2006; 18(4):605–11.
- 4) Naik TR, Kraus RN, Siddique R. CLSM containing a mixture of coal ash and a new pozzolanic material. *ACI Mater J* 2003; 100(3):208–15.
- 5) Etiegni L, Campbell AG. Physical and chemical characteristics of wood ash. *Bioresource Technol* 1991; 37(2):173–8
- 6) Naik, T.R., Kraus, R.N., and Siddique, R. (2002). “Demonstration of manufacturing technology for concrete and CLSM utilizing wood ash from Wisconsin.” Report no. CBU-2002- 30. Report for year 1 activities submitted to the Wisconsin Department of Natural Resources, Madison, WI, for Project # 01-06 UWM Center for By- Products Utilization, Department of Civil Engineering and Mechanics, University of Wisconsin-Milwaukee, Milwaukee, 124.
- 7) Madhavi TP, Sampathkumar V, Gunasekaran P. 2013. Partial replacement of cement and fine aggregate by Using fly ash and glass aggregate. *International Journal of Research in Engineering and Technology*.351-355
- 8) Kulkarni Anil., Kumar Rajeeb., Kumar Vikram., Comparison study on Natural River sand and crushed stone sand,
- 9) Vassilev SV, Baxter L, Anderson LK, Vassileva CG. An overview of the chemical composition of biomass. *Fuel* 2010; 89:913–33
- 10) Naik, T.R., Kraus, R.N., Chun, Y.M., Ramme, W.B., and Singh, S.S. (2003). “Properties of field manufactured cast-concrete products utilizing recycled materials.” *J. Mater. Civil Engg*, 15(4), 400–407.
- 11) American Standard for Testing and Materials, Standard Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use in Concrete, ASTM C 618-94, 1994.
- 12) Sosa Andres., Reynolds Byron., Vaosa Moreno., Dec 2014, FAMU – FSU College of Engineering, Study of Test methods for Fresh & hardened Concrete.
- 13) BSEN 12350 – 2, Determination of slump
- 14) BSEN 12390 – 3, Compressive strength of hardened concrete
- 15) SLS 1425 1 & 2, Specifications and Test methods for Concrete paving blocks

- 16) Abdullahi, M. (2006). "Characteristics of wood ash/OPC concrete." Leonardo Electronic Prac. Technol., 8, 9–16
- 17) Raheem AA, Adenuga OA. 2013. Wood Ash from Bread Bakery as Partial Replacement for Cement in Concrete. International Journal of Sustainable Construction Engineering and Technology 4(1):7581.
- 18) Rajput J, Yadav RK, Chandak R. 2013. The Effect of Rice Husk Ash used as Supplementary Cementing Material on Strength of Mortar. International Journal of Engineering Research and Applications 3(3):133-136.
- 19)] Rajamma Rejini, Ball Richard J, Tarelho Luis AC, Allen Geoff C, Labrincha Joao A, Ferreira Victor M. Characteristics and use of biomass fly ash in cement based materials. J Hazard Mater 2009;172(2009):1049–60.
- 20) Etiegni, L. (1990). "Wood ash recycling and land disposal." Ph.D. thesis. Department of Forest Products, University of Idaho at Moscow, Idaho, USA.