

REFERENCES

- [1] P. G. S. Gimhan, J. P. B. Disanayaka and M. C. M. Nasvui, "Suitability of fly ash produced at Lakvijaya coal power plant as a light weight embankment material," in *8th International Conference on Structural Engineering and Construction management*, Kandy, Sri Lanka, 2017.
- [2] J. J. Biernacki, A. K. Vazrala and H. W. Leimer, "sintering of class F fly ash," *Fuel*, vol. 87, pp. 782-792, 2008.
- [3] M. Ilic, C. Cheeseman, C. Sollars and j. Knight, "Mineralogy and microstructure of sintered lignite coal fly ash," *Fuel*, pp. 331-336, 2003.
- [4] R. Siddique, "Effect of fine aggregate replacement with class F fly ash on the abrasion resistace of concrete," *Cement and Concrete Research*, vol. 33, pp. 1877 - 1881, 2003.
- [5] J. Bijen, "Manufacturing process of artificial light weight aggregate from fly ash," *The International Journal of Cement Composite and Light weight Concrete*, vol. 8, no. 3, August 1986.
- [6] R. German, "Thermodynamics of sintering," *Sintering of Advanced Material*, pp. 3 - 32, 2010.
- [7] V. Adell, C. Cheeseman, A. Doel, A. Beattie and A. Boccaccini, "Comparison of rapid and slow sintered pulverised fuel ash," *Fuel*, vol. 87, pp. 187-195, 2008.
- [8] J. M. Fox, "Changes in fly ash with thermal treatment," *Material Science*, 2005.
- [9] C. M. Riley, "Relation of chemical properties to the bloating of clay," *Journal of the American ceremic society*, vol. 34, no. 4, pp. 121-128, 1951.
- [10] C. W. Tang, H. j. Chen, S. Y. Wang and J. Spaulding, "Poduction of synthetic lightweight agregate using reservoir sediments for concrete and masonary," *Cememt and Concrete Composites*, vol. 33, pp. 292-300, 2011.
- [11] S. Jaroslav and R. Zdenka, "Pelletization of fines, developements in mineral Processing.," *Elsevier*, vol. 7, 1988.
- [12] E. Uwe, A. Boccaccini, S. Cook and C. Cheeseman, "Effect of borate addition on the sintered properties of pulverised fuel ash," *Ceramicsinternational*, pp. 993-999, 2009.
- [13] K. Ramamurthy and K. Harikrishnan, "Influence of binderds on properties of sintered fly ash aggregate.," *Cement & Concrete Composite*, vol. 28, pp. 33-38, 2006.

- [14] P. Dharmasena, "Magnitude of sedimentation in village tanks," Trop. Agric. Dept. of Agric., Peradeniya, Sri Lanka, 1992.
- [15] U. P. Nawagamuwa and R. P. M. C. Senarathna, "Suitability of silt deposits of irrigation tanks in Angunakolapelessa, Sri Lanka for engineering applications," *ENGINEER*, vol. 3, pp. 59-67, 2018.
- [16] C. L. Hwang, L. A. T. Bui and C. T. Lo, "Manufacture and performance of lightweight aggregate from municipal solid waste incinerator fly ash and reservoir sediment for self consolidating light weight concrete," *Cement and Concrete Composites*, vol. 34, pp. 1159-1166, 2012.
- [17] D. Bentz and W. J. Weiss, "Internal curing; A 2010 State-of-the - Art Review," 2011.
- [18] R. Dhir, P. Hewlett, J. Lota and T. Dyer, "An investigation into the feasibility of formulating 'self-cure' concrete," *Material and Structures*, vol. 27, pp. 606-615, 1994.
- [19] O. M. Jensen and P. Lura, "Techniques and materials for internal water curing of concrete," *Materials and Structures*, vol. 39, p. 817–825, 2006.
- [20] D. Zou, K. Li, W. Li, H. Li and T. Cao, "Effect of pore structure and water absorption on internal curing efficiency of porous aggregates," *Construction and Building Materials*, vol. 163, pp. 949-959, 2018.
- [21] J. Castro, L. Keiser, M. Golias and J. Weiss, "Absorption and desorption properties of fine lightweight aggregate for application to internally cured concrete mixtures," *Cement & Concrete Composites*, vol. 33, p. 1001–1008, 2011.
- [22] T. Holm, O. Ooi and T. Bremner, "Moisture dynamics in lightweight aggregate and concrete," *Expanded Shale Clay and Slate Institute*, p. 12, 2004.
- [23] M. Bandara, W.K.Mampearachchi and T.Anojan, "Enhance the Properties of concrete using pre-developed burnt clay chips as internally curing concrete aggregate," *Case studies in Construction Materials*, vol. 11, 2019.
- [24] D. Shen, J. Jiang, J. Shen, P. Yoa and G. Jiang, "Influence of prewetted lightweight aggregates on the behaviour and cracking potential of internally cured concrete at an early age," *Construction and Building Materials*, vol. 99, pp. 260-271, 2015.
- [25] D. shen, M. Wang, Y. Chen, T. Wang and J. Zhang, "Prediction model for relative humidity of early-age internally cured concrete with pre-wetted light weight aggregates.," *Construction and Building Materials*, vol. 144, pp. 717-727, 2017.

- [26] R. Henkensiefken, P. Briatka, D. Bentz, T. Nantung and J. Weiss, "Plastic shrinkage cracking in internally cured mixtures made with pre-wetted light weight aggregate.," *Concrete International*, vol. 32, no. 2, pp. 49-54, 2010.
- [27] M. M. H. W. Bandara and W. K. Mampearachchi, "Mitigate the curing problems of concrete pavements by using heated non-expansive clay particles as internal curing agent," *Road Materials and Pavement Design*, 2019.
- [28] Á. Paul and M. Lopez, "Assessing Lightweight Aggregate Efficiency for Maximizing Internal Curing Performance," *ACI Material Journal*, pp. 385-393, July 2011.
- [29] J. Schlitter, R. Henkensiefken, J. Castro, K. Raoufi, J. Weiss and T. Nantung, "Development of Internally cured concrete for increased service life," 2010.
- [30] I. Donnelly, E. Jons and E. Webster, "Synthetic gravel from dry flue gas desulphurisation end product," in *Sixth International Ash Utilisation Symposium*, Reno Nevada, 1982.
- [31] C. Cheeseman, "Production of sintered lightweight aggregate using waste ash and other industrial residues," in *2nd International Slag Valorisation Symposium*, 2011.